

CERES



Ceres Enclosed Trailer
Models 6m and 5.5m





Contents:

1. Ceres Base models
2. Standard Equipment
3. Additional Equipment
4. Terms, Conditions and Contact

Ceres is available in two base models:

- **Ceres.55** - in standard equipped with 2 axles with R13C 195/50 wheels
- **Ceres.60** - in standard equipped with 3 axles with R10C 195/55 wheels

Running gear can be exchanged - 3 axles mounted on Ceres 55 and 2 axles mounted on Ceres 60

All standard equipment is valid for both versions.

Check Ceres presentation video [here!](#)

Visit our website - www.apex-group.pl





Parameter	Ceres.55	Ceres.60
Internal loading length	5500mm	6000mm
Internal loading width	2300mm	
Loading height measured in rear ramp	2010mm	
Running gear	3x1350kg 2x1800kg Al-Ko Axles 6x195/55 R10C 4x195/55R13C wheels	
Permissible total weight	3500kg	
Min. payload weight (equipment dependent)	2100kg	2000kg
Side walls openings size (LH & RH)	3300x1800mm	



Both models are in standard equipped with:

- fully aluminum chassis and deck, made out of closed section tubes - chassis and deck are fully welded
- main deck made out of 27mm thick, closed section aluminum panels - interior fully sealed from environment
- automatic support wheel in front
- spare wheel with custom cover
- fully electric, remote operated deck tilting
- deck mechanical central locking
- central controls via remote and panel located on B-Pillar
- full LED lighting
- flashing side markers lights
- warning lights on rear ramp doorframe top beam, controlled via remote
- repeated rear lights on rear ramp doorframe top beam
- 125 Ah AGM battery
- daylight roof made out of polycarbonate, milky white
- 25mm thick, sandwich composite side walls
- aerodynamic, composite front fairing
- side lift-up flaps with gas springs assistance on both LH and RH side.
 - Openings size: 3300x1700mm
 - Opening via single handle connected with automotive grade rotary locks
- hatches on front side walls.
 - Opening size: 600x750mm
 - Opening via single handle connected with automotive grade rotary locks
- rear ramp made out of 40mm thick, closed section aluminum profiles
 - Opening size: 2300x2010mm
 - Opening via single handle connected with automotive grade rotary locks

Standard models finish

- Inside and outside of side walls and roof are finished in white - RAL9016
- Bottom side skirts are finished in black - RAL9005



CERES

Code	Options - Technology & safety	Description
A.10	AL-KO AKS ball coupling	An advanced ball hitch with an integrated stabilization system that actively dampens vibrations and trailer "snaking," significantly improving driving safety and comfort.
A.20	Additional axle shock absorbers	Octagonal shaped absorbers effectively minimize hazardous trailer bounce during transit, ensuring a smoother ride, improved braking performance, consistent road contact, and maximum safety for both your vehicle and cargo.
A.30	Camera system	An integrated monitoring system, consisting of an internal camera and a reversing camera. It provides full visual control over the cargo during transport and eliminates blind spots while maneuvering.



Code	Options - Body & accessibility	Description
B.10.L B.10.R B.10.LR	Folding four leaf doors (one side)	Full-size, folding side doors, consisting of four panels. They provide maximum access to the transported vehicle while requiring minimal space to open. Possible to mount both on left and right hand side. Single folding pair opened via one, car-like handle.
B.20.L B.20.R B.20.LR	Full size inspection doors with parallel kinematics (one side)	A dedicated inspection door that facilitates access to the front of the cargo or to internally mounted equipment, without the need to open the main openings. Parallel, bus-like opening motion. Opened via car-like handle. Opening size is 750x1700mm



Code	Options - Cargo & usable space	Description
C.10	Internal cargo box	Internal cargo box in the front part of the trailer. Key-lockable, with flap opening assisted on gas springs. Capacity - 110 liters.
C.20.L C.20.R C.20.LR	External side cargo drawer (one side)	Side cargo drawer with a length of 1250mm, key-lockable.. Capacity - 90 liters. When ordering single drawer, please specify side of drawer mounting.
C.30	Wheel rack	Width of 1800mm, possibility to transport up to 8 wheels.



Code	Options - Power & electronics	Description
0.10	Light internal battery - LiFePo4	A modern and efficient lithium iron phosphate (LiFePO4) battery. It is characterized by a significantly longer lifespan, lower weight, and greater operational stability compared to traditional AGM batteries. Weights 20kg less than an AGM battery.
0.20	Winch	9500 LBS winch mounted under the deck, equipped with synthetic rope entering inside of trailer at the front of the deck. Winch remotely controlled via remote or control panel.
0.30	Internal LED Lighting	Additional LED interior lighting in the form of strips on the left and right sides of the trailer. Remote -controlled via remote or control panel.





Code	Options - Appearance & personalisation	Description
E.10	Alloy rims	Black, diamond-cut aluminum rims
E.20	External color painting/wrapping	Painting of all external trailer elements into desired RAL colour
E.30	Internal color painting/wrapping	Painting/wrapping in vinyl film internal walls and roof of trailer.
E.40	Deck protection painting	For clients working in harsh environments, we offer an optional full-deck polyurethane coating that significantly enhances scratch resistance while further improving the floor's anti-slip performance.





Terms and Conditions of Sale - Apex Group

1. To place an order, please contact our sales department by sending your inquiry or desired configuration to sales@apex-group.pl. All orders are considered official only after written confirmation from both parties via email.
2. **2. Payment Terms**
 - a. **Deposit:** A non-refundable deposit equivalent to 30% of the gross order value is required to secure the production slot and commence the manufacturing process.
 - b. **Final Payment:** The remaining balance of 70% must be settled in full before the scheduled collection date. The funds must be cleared in our bank account prior to the release of the trailer.
3. **3. Production and Lead Time**
 - a. The estimated production lead time is approximately 12 weeks from the date the deposit is received.
 - b. This timeframe is an estimate and may vary depending on the complexity of the configuration and current production schedules.
 - c. A definitive, estimated completion date will be provided to the customer upon order confirmation.
4. **4. Collection & Handover**
 - a. All trailers are to be collected from our production facility in Niewiadów, Poland (Ex-Works), unless otherwise agreed in writing.
 - b. The customer is responsible for arranging and covering the costs of transport.
 - c. Please contact us at least 5 business days in advance to schedule a collection appointment. Collection is possible during our standard business hours (Monday-Friday, 8:00 AM - 4:00 PM).
5. **5. Warranty**
 - a. All our products are covered by a manufacturer's warranty. The detailed warranty policy, including terms, conditions, and limitations, is published on our website: apex-group.pl. The terms available on the website are considered binding.

In case of any additional question - contact us

Piotr
p.psut@apex-group.pl
+48 726 922 707

Mateusz
m.rogala@apex-group.pl
+48 505 507 315

